


K4/K41 Beacon Waterproof Beacon



- Up to 4 years battery life
- Waterproof IP67, replaceable battery
- Additional accelerometer available
- iBeacon, Eddystone (UID, URL, TLM), KSensor broadcast at the same time
- All the parameters of this product can be modified via configuration App.



Description

K4/K41 Beacon is a waterproof beacon with ultra low power chipset nRF52 series and BLE 5.0 technology.

It has two screw holes, can be easily installed, K4/K41 has very strong signal. It has durable and industrial design, it can be used in harsh environment. K4/K41 is designed for commercial advertising and location-based service indoor or outdoor.

K4/K41 Beacon broadcasts 2.4GHz radio signals at regular and adjustable intervals. K4/K41 Beacon can communicate and intergrate with iOS, Android or other BLE4.0/5.0 enabled devices.

Specification

Size	Dia 38.6mm*15.7mm	BLE version	BLE4.0/BLE5.0
Material	ABS	Protocol	iBeacon/Eddystone/KSensor
Color	Black, white(Other colors can be customized)	OTA	Yes
Weight	25g (with battery)	Button	1 button internal
Battery	CR2477(replaceable)	LED	2 LEDs
Battery Life	48 months (Base on Broadcast Interval 1 second and TX power 0dBm)	Sensor	Accelerometer (for K4 only)
Transmit range	100 meters in open area	Buzzer	N/A
Waterproof	IP67	Working temperature	-40°C~+70°C
Chipset	Nordic nRF52 series	Accessory	1*3M sticker or 2*screw

Features

- Up to 4 years battery life, battery is replaceable
- Waterproof IP67
- Additional accelerometer available
- Support iBeacon/Eddystone/KSensor
- SDK or Library provided

Certification

- CE available
- FCC available

Product Details

suitable for printing or QR code



Holes for screws mounting

Compatibility

- Supported iOS 8.0+ and Android 4.3+ system.
- Compatible with Apple iBeacon standard.
- Compatible with all Bluetooth Low Energy 4.0/5.0 devices.

High quality and easy-to-replace battery

- CR2477 coin battery, commonly used and easy to replace.
- Easy to get the real-time battery level notification.

Configurable Parameters

- UUID, Major, Minor, Device Name, Device ID, Password, Advertising Interval, Tx Power etc.
- iOS and Android Configuration APP.

Transmission Power Levels

- Adjustable grades.
- Transmission power range: -40dBm to +4dBm.

Long Range

- Up to 100 meters in the open space;
- The range depends on the environment.

Security

- 16 Bytes encrypted password.
- Support Unconnectable Mode, prevent from malicious connections

OEM Service

- Logo and device color customizable;
- Provided with your own configuration (with MOQ).
- Additional optional sensors available
- We can also provide users with the same type of products with 3-axis accelerometer according to customer's needs.

Firmware Update

- Supported update via Over-The-Air (OTA)
- Reserved J-Link port on the board for programming.

Default Broadcast Content

- Device Name
- Mac Address
- iBeacon (Including UUID, Major, Minor)

Packing Information

Details	Inner Box (Battery is included)	Outer Carton (Battery is included)
Quantity	30pcs/box	300pcs/carton (10 inner boxes)
Net Weight	0.75KG	7.5KG
Gross Weight	0.89KG	9.4KG
Size	27.5*17.5*5cm	36*24*38cm



Configurable Parameters

Item	Default setting	Remark
Device Name	KBPro_XXXXXX	XXXXXX (ID) is a digit number
Adv Interval	1000ms	Configurable range: 100~10000ms
Tx Power	0dBm	Configurable range: -40dBm~4dBm
Measure Power	-59dBm	RSSI@1m
Connectable Mode	Yes	'Yes' means connectable, 'No' means unconnectable
Beacon Type	iBeacon	Configurable Beacon Types: iBeacon, URL, UID, TLM, KSensor
UUID	7777772E-6B6B-6D63-6E2E-636F6D000001	
Major	Major and Minor combination is unique	
Minor		
Namespace ID	0x00000000000000000001	
Serial ID	0x00000000000001	
Eddystone URL	www.kkmcn.com	
Password	0000000000000000	

Contact Information

KKM CO.,LTD

Address: 6A-3CDE, Baoneng Science and Technology Industrial Park, Long Hua district, Shenzhen, Guang Dong, China 518109.

Tel: 86-755-28370901 Fax:86-755-84851206

E-mail: sales@kkmcn.com

Website: www.kkmcn.com